

# SECUREGRIP 25 Synthetic Roof Underlayment

TopShield® SecureGrip 25 Synthetic Roof Underlayment is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated felt in sloped roof system construction.



### Highly Engineered

Providing an affordable secondary water-shedding barrier for your shingle roof system.

### Inorganic Construction

100% synthetic construction offers long term moisture protection - doesn't absorb water and is inert to mold growth.

### Advanced Surface Technologies

SecureWalk™ (top) and SecureGrip (back) create incredible walkability.

### Improves Project Outcome

Rolls out flat and does not wrinkle, eliminating customer callbacks.

### Easier Installation

33% more coverage per pass across the roof (vs 36" wide rolls).

### Superior Performance

Designed to perform under extreme weather conditions.

### Durable

Synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 3 months.

### Description

TopShield® SecureGrip25™ Synthetic Roof Underlayment is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated felt in sloped roof system construction.

### Uses

A cost effective roofing underlayment used beneath fiberglass and asphalt shingles, shakes, stone coated steel roofing shingles, synthetic slate or sloped installations of standing seam metal panels.

### Storage

Always store rolls upright on pallets (or in the cradled pallet they are shipped on) and in a dry protected area.

### Availability

SecureGrip Synthetic Felts are available throughout the United States. Check with your local representative for product availability.

### Compliance: Codes

- ASTM D4869 Type I, II, III, & IV
- ASTM D226 Type I, II
- U.L. Classified as a Prepared Roofing Accessory
- ICC-AC-188 - Intertek / WH #CCRR
- FBC
- CCRR
- Miami-Dade

PHYSICAL DATA	
Per Roll	48" X 250'
Material Per Roll	1000 sq. ft.
Squares Per Roll	10 squares
Weight Per Roll	24 lbs
Rolls Per Pallet	56 rolls
Wt Per Pallet	1,344 lbs
Limited Warranty	30 Years

SPECIFICATIONS (meets or exceeds applicable standards)		
	Standard	SecureGrip 25
Permeability	ASTM E96	06 perms
Water Transmission	ASTM D4869	Pass
Nail Sealability	ASTM D1970	Pass
Pliability	ASTM D226	Pass
Tear Strength	ASTM D4533	MD 25 lbs / CD 25 lbs
Tensile Strength	ASTM D751	MD 109 lbs / CD 87 lbs
Elongation	ASTM D751	MD 20% / CD 20%
Wt Per Square	ASTM D5261	2.3 lbs
Nominal Thickness	ASTM D5261	7 mils
Range of Temperature	-	- 40°F to 240°F
Fire Rating UL Class A	ASTM E108	Pass
Miami-Dade	#23-0801.03	
CCRR	#1045	
FBC	# FL42148	



Intertek



Scan QR code for more information

