



PHYSICAL DATA	
Per Roll	48″ X 250′
Material Per Roll	1000 sq. ft.
Squares Per Roll	10 squares
Weight Per Roll	24 lbs
<b>Rolls Per Pallet</b>	56 rolls
Wt Per Pallet	1,344 lbs
Limited Warranty	30 Years

Permeability

**Nail Sealability** 

**Tear Strength** 

Elongation

Miami-Dade

CCRR

FBC

Wt Per Square

**Nominal Thickness** 

**Range of Temperature** 

**Fire Rating UL Class A** 

**Tensile Strength** 

Pliability

Water Transmission

# SECUREGRIP 30 Synthetic Roof Underlayment

TopShield<sup>®</sup> SecureGrip 30 Synthetic Roof Underlayment is a synthetic roofdeck protection designed and manufactured to replace asphalt saturated felt in sloped roof system construction.

# **Rightly Engineered**

Barrier for your shingle roof system. Inorganic Construction Moisture protection - doesn't absorb water and is inert to mold growth. Advanced Surface Technologies SecureWalkTM (top) and SecureGrip (back) promotes exceptional walkability. Improves Project Outcome Eliminating customer callbacks. Easier Installation 33% more coverage per pass across the roof (vs 36" wide rolls). Superior Performance

Designed to perform under extreme weather conditions.

#### Durable

Synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 3 months.

#### Uses

SPECIFICATIONS (meets or exceeds applicable standards)

Standard

**ASTM D4869** 

**ASTM D1970** 

ASTM D226

**ASTM D4533** 

ASTM D751

ASTM D751

**ASTM D5261** 

**ASTM D5261** 

ASTM E108

#23-0801.03

# FL42148

#1045

ASTM E96

installations of standing seam metal panels.

06 perms

Pass

Pass

Pass

2.3 lbs

7 mils - 40°F to 240°F

Pass

SecureGrip 30

MD 25 lbs / CD 25 lbs MD 109 lbs / CD 87 lbs

MD 20% / CD 20%

# Storage

Always store rolls upright on pallets (or in the cradled pallet they are shipped on) and in a dry protected area.

# Availability

TopShield SecureGrip 30 Synthetic Felts are available throughout the United States. Check with your local representative for product availability.

### **Compliance: Codes**

- ASTM D4869 Type I, II, III, & IV
- ASTM D226 Type I & II
- U.L. Classified as a Prepared Roofing Accessory
- ICC-AC-188 Intertek
- FBC # FL42148
- CCRR #1045
- Miami-Dade #23-0801.03









Scan QR code for more information

