

# Metal Plates

## SEAM & INSULATION



SIZE & TYPE	PART NO.	PKG. QTY	PKG. WT.
2" Metal Seam Plate	TRUMP2000TD	1000/Bucket	27 lbs.
2.4" Barbed Metal Seam Plate	TRUMPB2400TS	1000/Bucket	52 lbs.
3" Metal Insulation Plate	TRUMP3000TS	1000/Bucket	37 lbs.

### PRODUCT DESCRIPTION

Metal Seam Plates are used to mechanically attach single-ply and modified bituminous roof membranes to the substrate. The plate's circular design and reinforcing ribs provide exceptional strength to resist wind uplift forces. Metal Seam Plates are made of Galvalume coated steel for excellent corrosion protection that meet the requirements of ASTM D 6294, FM 4470 and DIN 50018.

Metal Insulation Plates are used to mechanically attach insulation, coverboards and BUR base sheets to the substrate. The plate's circular design and reinforcing ribs provide exceptional strength to resist wind uplift forces. Metal Insulation Plates are made of Galvalume coated steel for excellent corrosion protection.

### COMPATIBLE ACCESSORIES

**2" Metal Seam Plate** is used within fully bonded seams to attach reinforced and non-reinforced single-ply membranes to the substrate.

**2.4" Metal Seam Plates** are used to attach reinforced single-ply and modified bituminous membranes to the substrate.

**3" Metal Insulation Plate** has a flat bottom and is used to attach roof coverboards, insulation, and BUR base sheets to the substrate.

### MATERIAL SPECIFICATIONS

Manufacturing Location: Cleveland, OH USA  
LEED® Eligible Recycled Content: 40%

### CODE APPROVALS & LISTINGS

- FM Global
- Miami-Dade County
- FBC Approved



2" Metal Seam Plate	
Thickness	0.030"
Diameter	2"
Hole Diameter	0.260"
Coating	AZ-55 Galvalume



2.4" Barbed Metal Seam Plate	
Thickness	0.040"
Diameter	2.4"
Hole Diameter	0.265"
Coating	AZ-55 Galvalume



3" Metal Insulation Plate	
Thickness	0.017"
Diameter	3"
Hole Diameter	0.260"
Coating	AZ-55 Galvalume



Scan the QR code to access additional information

